





"The most compact, reliable and robust industrial inkjet printer for packaging printing on the market"





MYLAN GROUP

Longduc Industrial Park, Travinh City, Travinh Province, Vietnam Tel: +84 743 846 997 - Fax: +84 743 846 998 Email: info@mylangroup.com - Website: www.mylangroup.com





VJETSTORE

No. 1.2, Floor 1, Block A Phu Hoang Anh, Section 1 Nguyen Huu Tho Street, Phuoc Kien Ward Nha Be Dictrict, Ho Chi Minh City, Vietnam Tel: +84 837 817 990 - Fax: +84 837 840 998 Email: info@vietstore.com - Website: www.vjetstore.com

VJET®1020 INKJET PRINTER

TECHNICAL SPECIFICATIONS

Plug and print with HP45 ink cartridge (Hewlett Packard TIJ2.5 inkjet technology)

Dimensions (LxWxH): 106x53x83mm / 4.17x2.09x3.27in

Weight: 450g (excluding cartridge)

Display: Automatic rotation 2.8" 256K colors TFT LCD display

Power Supply: AC 100V – 240V, 50/60Hz, 1.4A. Maximum power consumption: 48W

Mounting Brackets: Anti-shock mounting mechanism for printer protection

Throw Distance: Up to 6mm

STANDARD FEATURES

WIFI connection via smart phones and tablets using Android and iOS operating systems

Stand-alone operation with USB keyboard direct connection, or with PC control

AUX I/O port for external sensor, encoder and alarm kit connection

USB2.0 port for operating with PC, firmware loading and event log to report

operation history

Built-in photo sensor and automatic data back-up system

Nozzle switching and self-cleaning capabilities to extend cartridge lifetime

Store up to 100 messages on the printer's memory

Multi-level password protection: Operator, Technician, Administrator Multi-function PC software for synchronization control and management

Automatic recognition of inks (aqueous or solvent) and application of appropriate

printing parameters

Smart recognition of multiple external devices for synchronized control via PC software

Hot-swap: Circuit protection for quick cartridge changeover

Real time interface: reports current operation of printer to mobile devices

PRINTABILITY AND SPEEDS

Menu languages: English (default), Chinese, Japanese, French, German, Spanish,

Finnish, Thai, Russian, Arabic, Portuguese and Vietnamese

Printable characters: Windows true fonts

Message line with predictable data: up to 6 lines from 1 – 12.7mm

Printability: Alphanumeric, logos, date/time, expiry date, Julian date, shift code,

counter/lot box code, multiple types of variable barcodes, and database

Resolutions: Max 600x600dpi

Print speed: 150m/min @ 300x300dpi

Up to 5 levels of optical density

INK SOLUTIONS AND ACCESSORIES HydraJET®2016 series - Aqueous inks for porous media (42ml: Black, Cyan, Red) SoluJET®2200 series - Solvent inks for semi- and non-porous media (42ml: Black,

Blue, Red)

Mounting accessories are available at www.vjetstore.com

OPERATING TEMPERATURE AND WARRANTY

Operating temperature between 5°C and 60°C

12-month warranty for all equipment excluding consumable parts



Printmark Solution Co.,Ltd.

34/30 Moo.4 Soi Nak Niwat48 ,Nak Niwat Rd., Ladprao, Bangkok 10230 Tel.02-570-1749 Fax.02-570-1750 Email: info@printmarksolution.com

www.printmarksolution.com